

SECTION 1: Identification

Product identifier

Product name Unfired Grade A Lava
Substance name Hydrated Aluminum Silicate

Al₂Si₄O₁₀(OH)₂

Other names / synonyms Unfired Grade A Lava, A Lava, Wonderstone

Recommended use of the chemical and restrictions on use

Machining Blank for Technical Ceramic Component(s)

Supplier's details

Name Superior Technical Ceramics Address 600 Industrial Park Road St. Albans, Vermont 05478

USA

Telephone 802-527-7726 Fax 802-527-1181

Emergency phone number(s)

802-527-7726

SECTION 2: Hazard identification

This product is considered an article and does not pose any health hazard under normal use. The health effects listed below may be relevant when dust is generated during machining or other processing conditions.

Classification of the substance or mixture

- Carcinogenicity (chapter 3.6), Cat. 1
- Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 1

GHS label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H335 May cause respiratory irritation
H350i May cause cancer by inhalation.

H372 Causes damage to organs through prolonged or repeated exposure

Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

Other hazards which do not result in classification

This product has the potential of generating respirable dust during machining. Dust may contain respirable crystalline silica. Prolonged inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of lung fibrosis are cough and breathlessness. Control and monitor occupational exposure to respirable crystalline silica dust in accordance to federal, state and local laws.

SECTION 3: Composition/information on ingredients

Components

1. Pyrophyllite

Concentration 80 - 95 %

Other names / synonyms Pyrophyllite CAS no. 12269-78-2

2. Silica, crystalline (airborne particles of respirable size)

Concentration < 5 %

Other names / synonyms Quartz; Sand; Silica, crystalline (airborne particles of respirable size); Silicon

(IV) oxide

CAS no. 14808-60-7

SECTION 4: First-aid measures

Description of necessary first-aid measures

If inhaled Move to fresh air and consult with local medical personnel if discomfort

persists.

In case of skin contact Wash affected area with soap and water and consult with local medical

personnel if irritation persists.

In case of eye contact Flush with tepid water for a minimum of 15 minutes and consult with local

medical personnel if discomfort persists.

If swallowed Administer water to dilute, but not if person is unconscious. Consult with

local medical personnel if discomfort persists.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Use any means suitable for extinguishing surrounding fire.

Special protective actions for fire-fighters

Use protective clothing and breathing equipment appropriate for the surrounding fire and to protect against the dust that may be dispersed in the air.

SECTION 6: Accidental release measures

Methods and materials for containment and cleaning up

Any dust should be wet mopped or dry vacuumed.

SECTION 7: Handling and storage

Precautions for safe handling

Any dust should be wet mopped or dry vacuumed.

SECTION 8: Exposure controls/personal protection

Control parameters

1. Silica, crystalline quartz, respirable dust (CAS: 14808-60-7)

PEL (Inhalation): See Annotated Z-3 ppm (OSHA) OSHA Annotated Table Z-1, www.osha.gov

2. Silica, crystalline guartz, respirable dust (CAS: 14808-60-7)

PEL (Inhalation): See Annotated Z-3 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

3. Silica, crystalline quartz, respirable dust (CAS: 14808-60-7)

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

4. Silica, crystalline quartz, respirable dust (CAS: 14808-60-7)

REL (Inhalation): See Annotated Z-3 (NIOSH) OSHA Annotated Table Z-1, www.osha.gov

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety goggles in the presence of airborne dust.

Skin protection

Polymer gloves for prolonged dust exposure.

Respiratory protection

NIOSH/MSHA approved respirator for dust when exposure limit is exceeded.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form Gray, Pink or Tan Semi - Porous Solid

Odor Odorless
Odor threshold N/A

Hq N/A Melting point N/A Initial boiling point and boiling range N/A Flash point N/A Evaporation rate N/A Flammability (solid, gas) N/A Upper/lower flammability limits N/A Upper/lower explosive limits N/A Vapor pressure N/A

Vapor density N/A Relative density 2.3 g/cc

Solubility(ies) Insoluble in water

Partition coefficient: n-octanol/water N/A
Auto-ignition temperature N/A
Decomposition temperature N/A
Viscosity N/A
Explosive properties N/A
Oxidizing properties N/A

SECTION 10: Stability and reactivity

Chemical stability

Stable at room temperature. Emits gaseous carbon oxides and water vapor upon heating.

Possibility of hazardous reactions

Carbon monoxide or carbon dioxide can evolve upon heating.

SECTION 11: Toxicological information

Information on toxicological effects

Serious eye damage/irritation

See Section 2

Respiratory or skin sensitization

See Section 2

Carcinogenicity

See Section 2

STOT-repeated exposure

See Section 2

SECTION 12: Ecological information

No Applicable Information Found

SECTION 13: Disposal considerations

Disposal of the product

This material is not hazardous per 40 CFR 261. Consultation with federal, state and local officials is recommended before disposal.

SECTION 14: Transport information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information

US FEDERAL

TSCA

CAS# 12269-78-2 is Not listed on the TSCA inventory. CAS# 14808-60-7 is listed on the TSCA inventory.

SARA Section 302 Extremely Hazardous Substances

Substance Not Listed.

Section 313

Substance Not Listed.

OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

US STATE

CAS# 14808-60-7 can be found on the following state right to know lists:

Massachusetts, Pennsylvania, Texas.

Consult your state and local resources for further information.

California Prop 65

Crystalline Silica (airborne particles of respirable size) is classified as a substance known to the state of California to be a carcinogen.

SECTION 16: Other information

Further information/disclaimer

Although reasonable care has been taken to provide accurate and current information in preparation of this document, Superior Technical Ceramics extends no warranties, makes no representation and assumes no responsibility for any loss, damage, or injury of any kind which may result from reliance of information provided in this document by any person.

Preparation Information

Prepared by: Superior Technical Ceramics 1-802-527-7726 lab@ceramics.net

Prepared on: June 1, 2015

Last Revision: -- verified March 22, 2024